



TECHNICAL DATA SHEET



NAME: FIBERGLASS EPOXY PATCH - AQUA

PART NUMBER(S): PO11-A

PRODUCT DESCRIPTION:

Fiberglass Epoxy Patch - Aqua is a specialty epoxy putty for repairs to damp or wet areas and underwater surfaces. After mixing, it forms a polymer compound that may be applied underwater (fresh or salt) and will bond tenaciously to surfaces such as fiberglass, concrete, ceramic, glass, metal, wood, and many plastics. Once cured, the application can be drilled, sawed, sanded, carved, and painted.

Features and Benefits:

- Easy-to-use and mistake-proof
- Bonds instantly with superior strength
- Saves hundreds of dollars in repairs
- Belongs in every pool shed, boat and tackle box
- Resistant to chemicals, water, and temperature extremes.
- Contains no solvents or VOCs.
Non-flammable, releases no noxious fumes
- Won't shrink or pull away.

Patch:

- Dings
- Holes
- Gouges

Repair:

- Decks and hulls
- Pools, hot tubs and spa
- Marine recreational equipment
- Leaking gaskets, gutters, and tanks

Bond:

- Fiberglass
- Metal
- Wood
- Concrete
- Ceramic
- Glass
- Many plastics
- Works on wet surfaces even underwater.

Size:

7" (4 oz)

Shelf Life: store 75°F or cooler for up to 2 years.

Temperature Rating: -40°F to 250°F continuous.
-40°F to 300°F.

Chemical Resistance:

Resistant to hydrocarbons, ketones, alcohol, ester, halocarbons, aqueous salt solutions and dilute acids and bases.

DO NOT USE ON STRUCTURAL APPLICATIONS.

Quantities:

24 UNITS/CASE



WWW.GREENCHEMLABS.COM

CUSTOMER SERVICE: 1-800-946-3151 | FAX: 1-800-336-9068

