



TECHNICAL DATA SHEET



NAME: FIBERGLASS EPOXY PATCH - QUICK FIX

PART NUMBER(S): PO11-QF

PRODUCT DESCRIPTION:

Fiberglass Epoxy Patch - Quick Fix is a hand-mixable, fast-setting, epoxy putty for quick, permanent repairs to ceramics, glass, metals, concrete, wood, and numerous plastics. After mixing, it forms an industrial-strength polymer compound for numerous repairs around the home or workshop. After 60 minutes the application can be sawed, sanded, tapped, drilled, machined, filed, and painted.

Features and Benefits:

Each handy stick contains pre-measured portions of activator and base throughout — no measuring or mixing tools are necessary. The consistency (like modeling clay) eliminates drips and runs, facilitates adhesion to the substrate, and allows the material to be shaped and formed as needed before curing begins. Suitable for interior or exterior use, it is resistant to water, chemicals, and temperature extremes.

Fiberglass Epoxy Patch – Quick Fix contains no solvents or VOCs. It's non-flammable and releases no noxious fumes. It won't shrink or pull away. The unused portion stays fresh for future use when saved in its original package.

Screen reader support enabled.

Repair:

- Auto trim
- Concrete
- Bricks
- Broken or loose wall and floor tile
- Emergency repairs

Mend:

- Toys
- Appliances
- Lawn mowers
- Sports equipment
- Holes in auto bodies

Fabricate:

- Small parts
- Electrical connectors
- Taxidermy
- Knobs
- Missing detail

Shelf Life: At 75°F 24 months.

Temperature Rating: Continuous -40° to 250°F. Intermittent -40° to 300°F.

Chemical Resistance: Resistant to hydrocarbons, ketones, alcohols, esters, halocarbons, aqueous salt solutions and dilute acids and bases.

NOT INTENDED FOR STRUCTURAL APPLICATIONS.

Quantities:

24 UNITS/CASE



WWW.GREENCHEMLABS.COM

CUSTOMER SERVICE: 1-800-946-3151 | FAX: 1-800-336-9068

