



TECHNICAL DATA SHEET

NAME: PLUG PATTY

PART NUMBER(S): IM081

PRODUCT DESCRIPTION:

Plug Patty is a ready to use plug that works immediately and can be used on leaks, punctures or holes. It can be used on fuel tanks, drums, pipes and more. Plug Patty will still adhere if the surface is dirty or still has liquid flowing from it. Patch cracks and holes to form an immediate seal, then follow-up with epoxy to make a strong, temporary repair.

Features and Benefits:

- Resistant to pesticides and fuel.
- No surface preparation required, easily sticks to dirty or rusty surfaces.
- Premix is ready to use immediately.
- Primarily used for fuels and non-miscible solvents.
- Not recommended for plugging containers of antifreeze, acids, caustics, or oxidizers.
- Temperature: 32°F to 150°F
- Works with 3' head pressure.

Use on:

- Leaks
- Punctures
- Cracks
- Holes
- Oily surfaces.
- Dirty surfaces.
- Liquid flowing from void.
- Wet surfaces

Plugs:

- Drums
- Fuel Tanks
- Pipes

Directions:

No surface prep is required. Just take a handful and apply it directly over leaks, punctures and holes. It's ready to use right out of the container and is wrapped in airtight plastic in a plastic jar.

Size:

10 oz.

Quantities:

8 UNITS/CASE



WWW.GREENCHEMLABS.COM

CUSTOMER SERVICE: 1-800-946-3151 | FAX: 1-800-336-9068

